



NOTES:

1. GREENWAY WIDTHS SHALL BE 6 FT, 8 FT OR 10 FT
- IF REQUIRED, GRASSED SWALE SHALL BE ON UPHILL SIDE OF TRAIL DIRECTING DRAINAGE TO CULVERTS
3. CONTRACTOR IS RESPONSIBLE FOR RE-ESTABLISHING AND STABILIZATION OF SLOPES DISTURBED BY CONSTRUCTION
4. NO ABOVE GROUND UTILITIES OR UTILITY SURFACE COVERS, PLATES, MANHOLES SHALL BE LOCATED WITHIN TRAIL AND SHALL BE MINIMUM 2 FT FROM THE EDGE OF TRAIL. RAISED MANHOLES SHALL BE MINIMUM 4 FT FROM EDGE OF TRAIL WHERE FEASIBLE
5. ALL TRAILS SHALL BE LOCATED MINIMUM 5 FT FROM THE BACK OF CURB
6. SIDE SLOPES SHALL NOT EXCEED 3:1 UNLESS OTHERWISE APPROVED BY THE TOWN
7. CUT & FILL SLOPES SHALL TIE INTO EXISTING SLOPES TO CREATE AN EVEN TRANSITION
8. CROSS SLOPE TYPICALLY TO LOW SIDE BUT CROSS SLOPE TO INSIDE OF DOWNHILL CURVES, WITH GRADUAL TRANSITIONS BETWEEN ANY CROSS SLOPE DIRECTION CHANGES



EFFECTIVE: X/XX/21

STANDARD ASPHALT GREENWAY TRAIL

TOWN OF PITTSBORO

STANDARD CONSTRUCTION
DETAIL

STANDARD NO: GR-09-001